

## 【可変圧力式調整器性能表】

## RMA100 I

入口圧力 (MPa)	出口圧力 (MPa)	LPG流量 (kg/h)		
		5% offset	10% offset	20% offset
0.07	0.01	34.5	45.0	66.0
	0.02	45.0	82.5	105.0
	0.03	51.0	87.0	115.5
	0.04	49.5	90.0	105.0
	0.05	52.5	87.0	97.5
	0.06	43.5	76.5	96.0
0.10	0.01	69.0	76.5	99.0
	0.02	40.5	96.0	127.5
	0.03	52.5	112.5	150.0
	0.04	78.0	112.5	150.0
	0.05	84.0	120.0	145.5
	0.06	82.5	120.0	135.0
	0.07	75.0	105.0	135.0
	0.08	72.0	105.0	120.0
	0.09	55.5	90.0	112.5
0.20	0.01	90.0	127.5	165.0
	0.02	58.5	105.0	202.5
	0.03	58.5	150.0	225.0
	0.04	105.0	210.0	217.5
	0.05	120.0	195.0	225.0
	0.06	150.0	217.5	225.0
	0.07	135.0	202.5	225.0
	0.08	127.5	210.0	210.0
	0.09	157.5	210.0	210.0
	0.1	142.5	202.5	217.5

入口圧力 (MPa)	出口圧力 (MPa)	LPG流量 (kg/h)		
		5% offset	10% offset	20% offset
0.50	0.01	157.5	217.5	
	0.02	180.0	225.0	
	0.03	142.5	210.0	
	0.04	165.0	225.0	
	0.05	180.0	217.5	
	0.06	240.0	210.0	
	0.07	270.0	240.0	
	0.08	270.0	210.0	
	0.09	210.0	225.0	
	0.1	255.5	217.5	
1.00	0.01	90.0	165.0	
	0.02	180.0	200<	
	0.03	195.0	200<	
	0.04	180.0	200<	
	0.05	195.0	200<	
	0.06	200<		
	0.07	200<		
	0.08	200<		
	0.09	200<		
	0.1	200<		
1.56	0.01	200<		
	0.02	200<		
	0.03	200<		
	0.04	200<		
	0.05	200<		
	0.06	200<		
	0.07	200<		
	0.08	200<		
	0.09	200<		
	0.1	200<		

流量7.5 kg/h 時において出口圧力を設定する。