

【可変圧力式調整器性能表】

RMA100 II

入口圧力 (MPa)	出口圧力 (kPa)	LPG流量 (kg/h)		
		5% offset	10% offset	20% offset
0.025	2	22.5	25.5	33.0
	5	27.0	36.0	54.0
	10	58.5	73.5	78.0
	20	51.0	63.0	69.0
0.04	2	22.5	25.5	34.5
	5	27.0	37.5	61.5
	10	66.0	75.0	96.0
	20	54.0	78.0	96.0
0.05	2	21.8	27.0	36.0
	5	27.0	42.0	66.0
	10	93.0	102.0	109.5
	20	75.0	105.0	112.5
	40	73.5	84.0	93.0
0.06	2	23.3	27.0	35.3
	5	30.0	45.0	72.0
	10	84.0	96.0	105.0
	20	93.0	109.5	120.0
	40	84.0	96.0	105.0

入口圧力 (MPa)	出口圧力 (kPa)	LPG流量 (kg/h)		
		5% offset	10% offset	20% offset
0.07	2	22.5	25.5	34.5
	5	30.0	45.0	75.0
	10	90.0	105.0	127.5
	20	105.0	112.5	135.0
	40	105.0	115.5	120.0
0.10	2	21.8	27.8	37.5
	5	34.5	48.0	84.0
	10	105.0	127.5	165.0
	20	90.0	142.5	165.0
	40	112.5	150.0	157.5
0.20	2	23.3	27.8	45.0
	5	33.0	58.5	105.0
	10	157.5	187.5	225.0
	20	150.0	232.5	232.5
	40	210.0	210.0	210.0
0.40	2	24.0	27.0	58.5
	5	27.0	69.0	135.0
	10	90.0	150.0	255.0
	20	172.5	285.0	232.5
	40	232.5	210.0	210.0

流量 20 kg/h 時において出口圧力を設定する。