

【可変圧力式調整器性能表】

RMA30A I

入口圧力 (MPa)	出口圧力 (MPa)	LPG流量(kg/h)		
		5% offset	10% offset	20% offset
0.07	0.01	17.3	18.8	20.3
	0.02	15.0	19.5	27.0
	0.03	15.0	21.8	33.0
	0.04	17.3	25.5	35.3
	0.05	16.5	24.0	33.8
	0.06	16.5	24.0	33.0
0.10	0.01	13.5	15.0	18.0
	0.02	14.3	19.5	27.0
	0.03	15.0	21.0	36.0
	0.04	18.8	30.8	42.0
	0.05	18.8	28.5	45.0
	0.06	19.5	33.8	46.5
	0.07	22.5	33.0	45.0
	0.08	21.0	31.5	42.0
	0.09	19.5	26.3	37.5
	0.1			
0.20	0.01	16.5	18.8	21.0
	0.02	12.8	19.5	29.3
	0.03	15.0	24.0	36.0
	0.04	17.3	30.8	51.0
	0.05	21.8	33.0	60.0
	0.06	24.0	42.0	67.5
	0.07	24.0	42.0	73.5
	0.08	27.0	54.0	79.5
	0.09	35.3	57.0	84.0
	0.1	31.5	54.0	84.0

入口圧力 (MPa)	出口圧力 (MPa)	LPG流量(kg/h)		
		5% offset	10% offset	20% offset
0.50	0.01	18.8	20.3	26.3
	0.02	18.0	30.0	42.0
	0.03	21.0	36.0	57.0
	0.04	17.3	43.5	67.5
	0.05	31.5	46.5	76.5
	0.06	34.5	57.0	87.0
	0.07	36.0	60.0	99.0
	0.08	36.0	67.5	105.0
	0.09	45.0	69.0	109.5
	0.1	45.0	75.0	115.5
1.00	0.01	13.5	16.5	23.3
	0.02	19.5	31.5	57.0
	0.03	24.0	33.0	66.0
	0.04	21.8	48.0	72.0
	0.05	36.0	52.5	90.0
	0.06	32.3	63.0	96.0
	0.07	36.0	64.5	105.0
	0.08	60.0	87.0	75.0
	0.09	45.0	78.0	120.0
	0.1	51.0	84.0	120.0
1.56	0.01	19.5	22.5	25.5
	0.02	24.0	39.0	55.5
	0.03	30.0	49.5	73.5
	0.04	31.5	55.5	82.5
	0.05	32.3	55.5	90.0
	0.06	36.0	73.5	102.0
	0.07	45.0	81.0	105.0
	0.08	58.5	93.0	120.0
	0.09	52.5	93.0	120.0
	0.1	60.0	100.5	135.0

流量10 kg/h 時において出口圧力を設定する。