

【可変圧力式調整器性能表】

RMA30A II

入口圧力 (MPa)	出口圧力 (kPa)	LPG流量 (kg/h)		
		5% offset	10% offset	20% offset
0.025	2	8.0	8.3	9.8
	5	8.3	10.5	12.8
	10	13.5	16.5	21.0
	20	11.3	19.5	22.5
0.04	2	8.3	9.0	9.8
	5	8.3	9.0	11.3
	10	15.8	19.5	24.0
	20	16.5	21.8	27.0
0.05	2	8.0	8.3	9.0
	5	8.3	9.8	12.8
	10	16.5	18.8	28.5
	20	14.3	19.5	30.0
	40	17.3	21.0	25.5
0.06	2	7.8	8.0	9.0
	5	9.0	9.8	12.8
	10	15.8	18.0	27.0
	20	20.3	27.0	34.5
	40	17.3	26.3	31.5

入口圧力 (MPa)	出口圧力 (kPa)	LPG流量 (kg/h)		
		5% offset	10% offset	20% offset
0.07	2	8.0	8.3	9.0
	5	8.3	9.8	12.8
	10	17.3	21.0	25.5
	20	15.0	24.8	34.5
	40	18.8	31.5	39.0
0.10	2	8.3	9.0	9.8
	5	8.3	9.0	12.0
	10	20.3	21.8	36.8
	20	18.0	37.5	48.0
	40	27.0	45.0	54.0
0.20	2	8.3	8.6	9.8
	5	9.0	10.5	15.8
	10	16.5	20.3	33.8
	20	26.3	33.0	60.0
	40	31.5	58.5	84.0
0.40	2	8.3	9.0	10.5
	5	9.8	11.3	19.5
	10	19.5	31.5	40.5
	20	21.0	48.0	75.0
	40	45.0	72.0	105.0

流量7.5 kg/h 時において出口圧力を設定する。