

## 【可変圧力式調整器性能表】

## RMA70A I

入口圧力 (MPa)	出口圧力 (MPa)	LPG流量(kg/h)		
		5% offset	10% offset	20% offset
0.07	0.01	25.5	28.5	55.5
	0.02	48.0	78.0	99.0
	0.03	48.0	84.0	97.5
	0.04	43.5	78.0	102.0
	0.05	40.5	70.5	94.5
	0.06	36.0	63.0	82.5
0.10	0.01	37.5	57.0	75.0
	0.02	46.5	63.0	90.0
	0.03	54.0	91.5	112.5
	0.04	46.5	96.0	120.0
	0.05	52.5	85.5	120.0
	0.06	54.0	99.0	127.5
	0.07	55.5	93.0	120.0
	0.08	63.0	93.0	109.5
	0.09	34.5	73.5	103.5
0.20	0.01	36.0	42.0	63.0
	0.02	21.0	63.0	87.0
	0.03	42.0	81.0	109.5
	0.04	72.0	105.0	150.0
	0.05	57.0	93.0	150.0
	0.06	67.5	105.0	172.5
	0.07	85.5	109.5	195.0
	0.08	90.0	142.5	202.5
	0.09	84.0	142.5	210.0
	0.1	105.5	157.5	210.0

入口圧力 (MPa)	出口圧力 (MPa)	LPG流量(kg/h)		
		5% offset	10% offset	20% offset
0.50	0.01	70.5	78.0	90.0
	0.02	49.5	85.5	105.0
	0.03	63.0	102.0	142.5
	0.04	75.0	120.0	157.5
	0.05	88.5	120.0	180.0
	0.06	87.0	135.0	195.0
	0.07	96.0	142.5	225.0
	0.08	112.5	165.0	240.0
	0.09	96.0	165.0	262.5
	0.1	105.0	172.5	270.0
1.00	0.01	57.0	70.5	90.0
	0.02	42.0	72.0	87.0
	0.03	45.0	84.0	105.0
	0.04	75.0	105.0	150.0
	0.05	81.0	135.0	187.5
	0.06	90.0	135.0	210.0
	0.07	84.0	135.0	232.5
	0.08	112.5	187.5	255.0
	0.09	102.0	187.5	270.0
	0.1	99.0	165.0	285.0
1.56	0.01	72.0	90.0	102.5
	0.02	48.0	87.0	109.5
	0.03	60.0	97.5	157.5
	0.04	82.5	120.0	187.5
	0.05	87.0	127.5	202.5
	0.06	76.5	142.5	225.0
	0.07	96.0	157.5	255.0
	0.08	97.5	172.5	277.5
	0.09	78.0	172.5	285.0
	0.1	142.5	217.5	330.0

流量10 kg/h 時において出口圧力を設定する。