

【可変圧力式調整器性能表】

RMA70A II

入口圧力 (MPa)	出口圧力 (kPa)	LPG流量(kg/h)		
		5% offset	10% offset	20% offset
0.025	2	18.8	19.5	22.5
	5	18.8	25.5	45.0
	10	48.0	60.0	72.0
	20	43.5	58.5	69.0
0.04	2	20.3	22.5	29.3
	5	23.3	30.8	52.5
	10	60.0	78.0	87.0
	20	67.5	85.5	90.0
0.05	2	21.0	25.5	33.0
	5	24.8	30.8	46.5
	10	75.0	88.5	99.0
	20	70.5	90.0	100.5
	40	49.5	60.0	75.0
0.06	2	22.5	25.5	32.3
	5	27.0	35.3	49.5
	10	99.0	105.0	109.5
	20	61.5	102.0	109.5
	40	69.0	90.0	97.5

入口圧力 (MPa)	出口圧力 (kPa)	LPG流量(kg/h)		
		5% offset	10% offset	20% offset
0.07	2	19.5	24.0	31.5
	5	21.0	30.8	51.0
	10	54.0	90.0	112.5
	20	64.5	105.0	120.0
	40	60.0	99.0	105.0
0.10	2	20.3	23.3	33.8
	5	24.0	34.5	57.0
	10	82.5	112.5	135.0
	20	105.0	135.0	157.5
	40	93.0	135.0	145.5
0.20	2	20.3	24.0	31.5
	5	21.0	34.5	63.0
	10	78.0	97.5	135.0
	20	102.0	157.5	202.5
	40	93.0	202.5	225.0
0.40	2	21.8	28.5	42.0
	5	31.5	45.0	75.0
	10	90.0	112.5	150.0
	20	120.0	180.0	232.5
	40	150.0	210.0	270.0

流量18 kg/h 時において出口圧力を設定する。